



DAF

FRONT-MOUNTED BRUSHCUTTER-MULCHERS

SPECIFICATIONS	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Recommended minimum carrier power	190 kW (250 hp) and up	150 kW (200 hp) and up	130 kW (175 hp) and up	95 kW (125 hp) and up	65 kW (85 hp) and up	60 kW (75 hp) and up
Cutting width	251cm (99 inch)	216 cm (85 in)	222 cm (88 inch)	189 cm (74 inch)	189 cm (74 inch)	150 cm (59 inch)
Cutting distance from ground level	3 cm (1 in)	3 cm (1 in)	3 cm (1 in)	3 cm (1 in)	3 cm (1 in)	3 cm (1 in)
Number of blades	35	31	31	27	27	21
Target material diameter	60 cm (24 in)	60 cm (24 in)	40 cm (15 in)	25 cm (10 in)	20 cm (8 in)	15 cm (6 in)
Exterior width	297 cm (117 in)	258 cm (102 in)	254 cm (100 in)	223 cm (88 in)	219 cm (86 in)	186 cm (73 in)
Height (with pushbar)	149 cm (59 in)	148 cm (58 in)	140 cm (55 in)	141 cm (55 in)	138 cm (54 in)	148 cm (58 in)
Height (no pushbar)	98 cm (38 in)	96 cm (38 in)	98 cm (38 in)	94 cm (37 in)	112 cm (44 in)	66 cm (26 in)
Depth (with pushbar)	125 cm (49 in)	130 cm (51 in)	139 cm (55 in)	115 cm (45 in)	129 cm (51 in)	107 cm (42 in)
Depth (no pushbar)	83 cm (33 in)	83 cm (33 in)	83 cm (33 in)	69 cm (27 in)	79 cm (31 in)	72 cm (29 in)
Rotor diameter	51 cm (20 in)	51 cm (20 in)	51 cm (20 in)	51 cm (20 in)	46 cm (18 in)	46 cm (18 in)
Weight	2430 kg (5360 lb)	2300 kg (5100 lb)	1985 kg (4380 lb)	1365 kg (3010 lb)	1185 kg (2610 lb)	1100 kg (2400 lb)

HYDRAULIC SYSTEM	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Variable displacement axial piston motor	2x 107cc	2x 107cc	1x 170cc	1x 107cc	1x 107cc	1x 80 cc
Minimum required continuous flow	265 l/min (70 gal/min)	230 l/min (60 gal/min)	190 l/min (50 gal/min)	150 l/min (40 gal/min)	115 l/min (30 gal/min)	85 l/min (20 gal/min)
Operating pressure	3500 psi (240 bar)	3500 psi (240 bar)	3500 psi (240 bar)	3500 psi (240 bar)	3500 psi (240 bar)	3500 psi (240 bar)
Rotating speed	2500 rpm	2500 rpm	2500 rpm	2500 rpm	2500 rpm	2500 rpm
Pressure line	#20 (1.25 in)	#20 (1.25 in)	#16 (1.00 in)	#16 (1.00 in)	#16 (1.00 in)	#12 (0.75 in)
Return line	#20 (1.25 in)	#20 (1.25 in)	#16 (1.00 in)	#16 (1.00 in)	#16 (1.00 in)	#12 (0.75 in)
Drain line	#16 (1.00 in)	#16 (1.00 in)	#12 (0.75 in)	#10 (0.675 in)	#10 (0.675 in)	#8 (0.5 in)

OPTIONS	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Type of bolt-on, forged, sharpenable blades	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic pushbar	✓	✓	✓	✓	✓	✓
Upgradable motor	✗	✗	✗	✓	✗	✓

Those are minimum requirements; call your DENIS CIMAF's Sale Representative for guidance in selecting the best match. This information is subject to change without notice.

CONTACT US

211 rue Notre-Dame
Roxton Falls QC J0H 1E0
Canada
www.deniscimaf.com

Toll free : 877-279-2300
Phone : 450-548-7007
Fax: 450-548-7008
info@deniscimaf.com

DENIS  **CIMAF**