



DAH

BOOM-MOUNTED MULCHERS

SPECIFICATIONS	DAH-150Er	DAH-150E	DAH-125D	DAH-100C	DAH-085B	DAH-065B
Excavator Size [t (lbs)]	27 - 35 (54000 - 70000)	20 - 27 (40000 - 54000)	16 - 22 (32000 - 44000)	10 - 15 (20000 - 30000)	8 - 10 (16000 - 20000)	5 - 8 (10000 - 16000)
Recommended Minimum Carrier Power [kW (hp)]	142 (192)	96 (130)	59 (80)	48 (65)	40 (54)	37 (50)
Cutting width [cm (in)]	145 (57)	145 (57)	121 (48)	108 (42)	87 (34)	65 (26)
Cutting Distance from Ground Level [cm (in)]	2 (0.75)	2 (0.75)	2 (0.75)	2 (0.75)	2 (0.75)	2 (0.75)
Number of Blades on Rotor	21	21	17	15	15	11
Optimal Target Material Diameter [cm (in)]	50 (20)	40 (15)	25 (10)	15 (6)	10 (4)	≤ 10 (4)
Exterior Length [cm (in)]	200 (79)	200 (79)	165 (65)	152 (60)	120 (47)	100 (39)
Exterior Height [cm (in)]	119 (47)	112 (44)	96 (38)	127 (50)	79 (31)	84 (44)
Exterior Width [cm (in)]	81 (32)	81 (32)	74 (29)	76 (30)	66 (26)	66 (26)
Rotor Diameter [cm (in)]	51 (20)	51 (20)	46 (18)	43 (17)	35 (14)	35 (14)
Approximate Typical Weight [kg (lbs)]	1700 (3740)	1530 (3370)	1005 (2220)	715 (1570)	510 (1120)	420 (920)

HYDRAULIC SYSTEM	DAH-150Er	DAH-150E	DAH-125D	DAH-100C	DAH-085B	DAH-065B
Variable Displacement Axial Piston Motor [cc]	170	115	115	85	60	28
Min. Required Continuous Flow [L/min (gal/min)]	205 (54)	136 (36)	121 (32)	102 (27)	95 (25)	45 (12)
Max. Operating Pressure [bar (psi)]	350 (5000)	350 (5000)	350 (5000)	350 (5000)	275 (4000)	275 (4000)
Rotating Speed [rpm]	3000	3000	3000	3000	4000	4000
Pressure Line I.D. [# (in)]	#20 (1.25)	#16 (1.00)	#16 (1.00)	#12 (0.75)	#10 (0.625)	#10 (0.625)
Return Line I.D. [# (in)]	#20 (1.25)	#16 (1.00)	#16 (1.00)	#12 (0.75)	#10 (0.625)	#10 (0.625)
Drain Line I.D. [# (in)]	#12 (0.75)	#12 (0.75)	#12 (0.75)	#12 (0.75)	#8 (0.50)	#8 (0.50)

FEATURES	DAH-150Er	DAH-150E	DAH-125D	DAH-100C	DAH-085B	DAH-065B
Type of Sharpenable Bolt-on Forged Blades	Standard	Standard	Standard	Standard	V-back	V-back
Tilt System	✓	✓	✓	✓	✓	✗
Bolt-on Wear Liner	✓	✓	✗	✓	✗	✗
Approximate Weight (All Options) [kg (lbs)]	2100 (4640)	1865 (4100)	1320 (2900)	910 (2000)	545 (1200)	455 (1000)

These are minimum requirements; call your DENIS CIMAF's Sale Representative for guidance in selecting the best match. This information is subject to change without notice.

CONTACT US

Printed in Canada : 2018-02

211 rue Notre-Dame
Roxton Falls QC J0H 1E0
Canada
www.deniscimaf.com

Toll free : 877-279-2300
Phone : 450-548-7007
Fax: 450-548-7008
info@deniscimaf.com

DENIS  **CIMAF**